

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	1065.6 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	76.8V x 75.0H
	At 50% of Imax	64.8V x 65.0H
	At 90% of Imax	33.5V x 34.9H

Beam Flux	Total	992.3 lumens per klm.
	To 10% of Imax	934.5 lumens per klm.
	To 50% of Imax	804.7 lumens per klm.
	To 90% of Imax	270.2 lumens per klm.

Upward LOR	0.0 %
Downward LOR	99.2 %


Luminaire Efficiency (Light Output Ratio)	100.0 %
---	---------

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017-11-09

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:7.290m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.5V I:0.9461A P:203.5W PF:0.9751 Lamp Flux:30646.7x1 lm		
NAME: FL-5050-200	TYPE:LED	WEIGHT:24KG
SPEC.:C470SP-Q2-P-03A 230V50HZ	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



DATA OF LAMP		Eff:150.63lm/W	
MODEL	FL-5050-200-60	Imax(cd)	32656
NOMINAL POWER(W)	200	AVAILABILITY(%)	94.5
RATED VOLTAGE(V)	220	Avai. FLUX(lm)	28975
NOMINAL FLUX(lm)	30646.7	LOR(%)	100.0
LAMPS INSIDE	1	TOTAL FLUX(lm)	30647
TEST VOLTAGE(V)	220	θ @50% (H,V)	65,65DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm				Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		
90	0.06	0.31	0.76	1.41	2.23	3.25	3.92	4.13	4.31	4.31	4.11	3.89	3.23	2.21	1.40	0.75	0.30	0.06	40.6	0.00		
80	0.07	0.44	1.15	2.14	3.24	4.45	5.63	6.21	6.66	6.65	6.19	5.57	4.43	3.27	2.18	1.20	0.47	0.08	60.0	0.00		
70	0.09	0.61	1.59	2.86	4.38	6.22	8.19	9.45	10.2	10.2	9.43	8.18	6.26	4.49	3.00	1.73	0.71	0.13	87.7	0.00		
60	0.12	0.76	1.92	3.55	5.82	8.63	11.4	14.1	18.7	18.6	14.1	11.5	8.85	6.14	3.90	2.23	0.97	0.19	131	0.00		
50	0.14	0.89	2.21	4.33	7.43	11.3	42.9	183	255	255	179	41.5	11.8	8.07	4.97	2.73	1.22	0.25	1012	864		
40	0.16	1.00	2.48	5.06	8.89	31.1	258	627	791	788	614	243	28.9	9.93	6.07	3.26	1.47	0.30	3420	3324		
30	0.17	1.09	2.72	5.65	10.1	118	623	842	927	920	825	593	110	11.5	6.93	3.70	1.66	0.34	5002	4924		
-30	0.18	1.16	2.92	5.96	10.7	239	702	895	982	976	878	683	225	12.6	7.42	4.00	1.78	0.36	5627	5556		
	0.17	1.18	3.00	6.02	11.0	239	688	884	971	965	867	667	220	12.7	7.41	4.02	1.77	0.35	5550	5477		
	0.18	1.15	2.83	5.89	10.6	122	573	801	893	887	787	555	119	12.0	7.09	3.74	1.65	0.31	4781	4701		
	0.20	1.18	2.89	5.84	10.6	23.5	289	578	713	708	567	271	20.2	11.3	6.66	3.51	1.52	0.29	3214	3116		
	0.23	1.23	2.97	5.78	10.2	13.5	22.9	195	334	332	192	21.8	14.0	10.6	6.25	3.36	1.44	0.28	1167	1012		
-40	0.26	1.28	3.06	5.67	9.59	14.5	15.3	11.8	12.3	12.3	11.7	15.3	14.3	9.53	5.78	3.21	1.37	0.29	147	0.00		
-50	0.28	1.27	2.98	5.32	8.36	12.1	15.7	18.3	19.4	19.4	18.1	15.5	11.9	8.22	5.29	3.00	1.29	0.29	167	0.00		
-60	0.28	1.17	2.61	4.55	6.80	9.23	11.8	13.4	14.4	14.4	13.3	11.6	9.05	6.66	4.47	2.57	1.14	0.28	128	0.00		
-70	0.25	0.94	1.94	3.25	4.76	6.37	7.64	8.41	8.90	8.92	8.43	7.64	6.37	4.75	3.25	1.95	0.95	0.25	85.0	0.00		
-80	0.11	0.36	0.69	1.08	1.51	2.02	2.36	2.47	2.55	2.57	2.51	2.40	2.05	1.52	1.09	0.71	0.38	0.11	26.5	0.00		
-90	-90	-80	-70	-60	-50	-40	-30	-20	HORIZONTAL (DEG)				20	30	40	50	60	70	80	90		
Φ t	2.93	16.0	38.7	74.4	126	865	3281	5093	5963	5930	4997	3158	814	136	83.2	45.7	20.1	4.15	30647	---		
Φ a	0.00	0.00	0.00	0.00	0.00	682	3141	4977	5844	5811	4883	3015	621	0.00	0.00	0.00	0.00	0.00	---	28975		

one-half-peak spread: U:32.1,D:32.9 , L:31.8,R:33.3


NEMA Beam Type: Type 5

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017-11-09

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:7.290m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:220.5V I:0.9461A P:203.5W PF:0.9751 Lamp Flux:30646.7x1 lm		
NAME: FL-5050-200	TYPE:LED	WEIGHT:24KG
SPEC.:C470SP-Q2-P-03A 230V50HZ	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017-11-09

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:7.290m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


Test:U:220.5V I:0.9461A P:203.5W PF:0.9751 Lamp Flux:30646.7x1 lm		
NAME: FL-5050-200	TYPE:LED	WEIGHT:24KG
SPEC.:C470SP-Q2-P-03A 230V50HZ	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017-11-09

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:7.290m [K=1.0000]
Remarks:

Planar Illuminance Curve




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017-11-09

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:7.290m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.5V I:0.9461A P:203.5W PF:0.9751 Lamp Flux:30646.7x1 lm		
NAME: FL-5050-200	TYPE:LED	WEIGHT:24KG
SPEC.:C470SP-Q2-P-03A 230V50HZ	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range: -90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2017-11-09

V(B) Range: -80 - 80DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 7.290m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.5V I:0.9461A P:203.5W PF:0.9751 Lamp Flux:30646.7x1 lm		
NAME: FL-5050-200	TYPE:LED	WEIGHT:24KG
SPEC.:C470SP-Q2-P-03A 230V50HZ	DIM.:	SERIAL No.:1
MFR.: EVERFINE	SUR.:	Shielding Angle:

Table--1

UNIT: ×10cd

H (DEG) V (DEG)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	7.45	8.20	8.94	9.92	10.9	12.0	13.2	14.3	15.4	16.6	17.8	19.3	20.4	20.7	20.7	20.8	21.0	21.1	21.2
-75	7.83	8.88	10.1	11.6	13.1	14.8	16.5	18.4	20.2	21.8	23.5	25.3	27.1	27.8	28.3	28.8	29.3	29.6	29.8
-70	8.22	9.55	11.2	13.2	15.3	17.5	19.8	22.4	24.9	27.1	29.2	31.4	33.9	34.9	35.8	36.8	37.6	38.1	38.4
-65	8.33	9.84	11.8	14.3	16.9	19.7	22.6	25.5	28.4	31.3	34.1	36.9	40.3	42.6	44.0	45.6	46.7	47.4	47.7
-60	8.44	10.1	12.4	15.4	18.5	21.9	25.4	28.6	32.0	35.4	38.9	42.4	46.7	50.3	52.3	54.4	55.8	56.7	57.1
-55	8.13	9.78	12.4	15.6	19.1	22.8	26.4	30.1	34.1	38.5	43.2	48.0	52.9	57.0	59.8	62.3	64.1	65.2	65.5
-50	7.82	9.43	12.3	15.9	19.7	23.6	27.3	31.5	36.2	41.5	47.5	53.7	59.2	63.8	67.4	70.3	72.4	73.6	74.0
-45	7.10	8.71	11.9	15.7	19.7	23.5	27.4	32.1	37.5	43.9	50.8	57.7	64.0	69.6	74.3	78.4	82.3	85.9	87.5
-40	6.38	7.99	11.6	15.5	19.6	23.3	27.5	32.6	38.9	46.3	54.1	61.8	68.8	75.4	81.2	86.6	92.2	98.1	101
-35	5.57	7.20	11.1	15.2	19.1	22.8	27.3	32.7	39.4	47.2	55.7	64.6	74.4	127	359	691	901	995	1022
-30	4.77	6.40	10.6	14.9	18.6	22.3	27.1	32.8	39.9	48.0	57.3	67.4	79.9	179	636	1295	1711	1892	1942
-25	4.03	5.81	10.4	14.8	18.2	22.1	27.1	33.0	40.1	48.4	58.6	87.0	401	975	1437	1894	2177	2310	2346
-20	3.29	5.23	10.2	14.7	17.9	21.8	27.1	33.2	40.4	48.7	59.8	107	722	1772	2238	2493	2644	2728	2749
-15	2.74	4.90	10.0	14.6	17.7	21.8	27.2	33.4	40.6	49.0	64.0	337	1269	2081	2472	2703	2845	2922	2941
-10	2.20	4.57	9.89	14.5	17.5	21.7	27.2	33.5	40.7	49.2	68.1	567	1816	2391	2705	2913	3046	3116	3133
-5	2.00	4.75	10.0	14.7	17.9	22.7	27.6	33.8	41.1	49.8	81.9	763	1962	2482	2783	2989	3119	3184	3199
0	1.79	4.92	10.2	14.9	18.3	23.6	28.0	34.1	41.5	50.3	95.6	959	2109	2572	2861	3065	3191	3253	3265
5	1.74	4.95	10.0	14.5	17.7	22.5	27.5	33.6	40.8	49.3	82.3	797	2007	2512	2812	3020	3150	3215	3229
10	1.69	4.99	9.86	14.2	17.2	21.4	26.9	33.0	40.1	48.3	69.0	636	1905	2451	2762	2975	3109	3178	3193
15	1.61	4.89	9.58	13.7	16.6	20.6	25.9	31.8	38.5	46.2	61.0	377	1404	2199	2564	2793	2936	3013	3032
20	1.53	4.80	9.30	13.2	16.1	19.9	24.9	30.6	37.0	44.1	53.1	119	903	1946	2365	2611	2763	2848	2870
25	1.43	4.49	8.77	12.5	15.4	18.9	23.4	28.6	34.5	40.9	48.5	85.0	483	1095	1639	2112	2353	2471	2502
30	1.34	4.19	8.23	11.7	14.7	17.8	21.9	26.7	32.0	37.7	44.0	50.7	64.0	244	913	1613	1942	2093	2134
35	1.24	3.90	7.72	11.0	14.0	16.8	20.4	24.5	29.2	34.3	39.6	45.2	54.0	146	483	835	1006	1093	1120
40	1.14	3.62	7.20	10.3	13.3	15.9	18.9	22.4	26.4	30.9	35.2	39.7	44.0	48.2	52.7	57.9	70.4	93.6	105
45	1.08	3.25	6.55	9.33	12.2	14.7	17.3	20.2	23.4	27.1	30.9	34.7	38.3	41.7	45.0	48.5	55.3	67.3	73.4
50	1.03	2.88	5.90	8.40	11.1	13.5	15.7	18.1	20.5	23.3	26.6	29.8	32.7	35.2	37.3	39.0	40.3	41.0	41.3
55	1.02	2.56	5.19	7.48	9.82	12.1	14.2	16.2	18.2	20.4	22.8	25.2	28.1	30.0	31.3	32.6	33.6	34.1	34.4
60	1.01	2.25	4.47	6.56	8.56	10.8	12.7	14.3	15.9	17.4	19.0	20.6	23.5	24.9	25.3	26.2	26.8	27.2	27.5
65	1.02	1.96	3.71	5.43	7.12	8.94	10.6	12.1	13.6	14.9	16.2	17.6	20.0	20.6	20.8	21.4	21.9	22.2	22.5
70	1.04	1.68	2.94	4.29	5.68	7.10	8.38	9.94	11.4	12.4	13.4	14.6	16.5	16.3	16.2	16.6	16.9	17.1	17.5
75	1.06	1.53	2.38	3.38	4.38	5.38	6.32	7.44	8.51	9.43	10.5	11.6	12.9	12.8	12.6	12.8	12.9	13.0	13.2
80	1.08	1.39	1.82	2.47	3.07	3.66	4.27	4.93	5.65	6.46	7.52	8.56	9.35	9.27	9.00	8.93	8.93	8.90	8.90
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017-11-09

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:7.290m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.5V I:0.9461A P:203.5W PF:0.9751 Lamp Flux:30646.7x1 lm																		
NAME: FL-5050-200									TYPE:LED					WEIGHT:24KG				
SPEC.:C470SP-Q2-P-03A 230V50HZ									DIM.:					SERIAL No.:1				
MFR.: EVERFINE									SUR.:					Shielding Angle:				

Table--2

UNIT: ×10cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-80	21.2	21.1	21.0	20.9	20.9	20.6	19.4	17.9	16.6	15.5	14.4	13.3	12.3	11.3	10.3	9.43	8.44	7.63	
-75	29.6	29.3	28.9	28.3	27.8	27.1	25.3	23.5	21.7	20.1	18.3	16.6	14.8	13.3	11.8	10.3	8.97	7.87	
-70	38.1	37.5	36.7	35.7	34.7	33.5	31.2	29.0	26.8	24.7	22.2	19.9	17.4	15.4	13.2	11.2	9.49	8.12	
-65	47.3	46.5	45.3	43.6	41.9	39.6	36.3	33.5	30.7	28.0	25.2	22.5	19.5	16.8	14.2	11.7	9.82	8.37	
-60	56.5	55.5	53.9	51.6	49.2	45.6	41.5	38.0	34.6	31.4	28.2	25.1	21.7	18.3	15.1	12.3	10.1	8.63	
-55	65.0	63.8	61.9	59.2	56.1	52.1	47.2	42.5	37.9	33.7	30.0	26.5	23.0	19.4	15.8	12.6	10.1	8.65	
-50	73.5	72.1	69.8	66.8	63.1	58.5	53.0	47.0	41.1	36.0	31.8	27.9	24.3	20.5	16.5	12.9	10.2	8.67	
-45	85.3	81.7	78.0	73.9	69.1	63.6	57.3	50.5	43.9	37.9	32.9	28.6	24.8	21.0	17.0	13.0	9.89	8.38	
-40	97.2	91.3	86.2	80.9	75.1	68.7	61.6	54.0	46.6	39.7	34.0	29.3	25.2	21.5	17.4	13.1	9.62	8.08	
-35	989	891	683	332	126	74.9	65.5	56.9	48.7	41.5	35.4	30.2	25.8	22.0	18.0	13.4	9.43	7.68	
-30	1881	1690	1281	584	177	81.0	69.3	59.7	50.8	43.3	36.7	31.1	26.4	22.6	18.6	13.7	9.23	7.28	
-25	2295	2150	1862	1378	923	347	89.2	61.7	52.2	44.5	37.8	32.0	27.0	23.0	19.2	14.2	9.27	7.07	
-20	2710	2610	2444	2172	1668	612	109	63.6	53.5	45.7	38.9	32.9	27.6	23.4	19.9	14.6	9.30	6.87	
-15	2903	2809	2653	2409	1999	1194	314	69.1	54.9	46.9	40.1	34.1	28.6	24.2	20.8	15.5	9.86	7.08	
-10	3097	3009	2862	2645	2330	1776	518	74.5	56.3	48.1	41.3	35.3	29.5	25.0	21.8	16.3	10.4	7.29	
-5	3166	3079	2931	2714	2408	1893	687	90.9	56.8	48.7	41.8	35.9	30.5	25.6	22.2	16.8	10.9	7.49	
0	3234	3150	3000	2782	2487	2010	856	107	57.3	49.2	42.3	36.5	31.4	26.2	22.7	17.3	11.3	7.69	
5	3197	3111	2961	2740	2435	1931	720	91.8	56.4	48.5	41.7	35.9	30.6	25.7	22.3	17.2	11.4	7.64	
10	3161	3072	2921	2698	2383	1852	584	76.3	55.4	47.8	41.2	35.3	29.7	25.2	22.0	17.0	11.5	7.59	
15	2994	2898	2738	2495	2107	1309	349	67.1	52.5	45.4	39.2	33.5	28.2	24.0	20.9	16.2	11.0	7.27	
20	2828	2724	2555	2292	1830	766	114	57.8	49.5	43.1	37.2	31.7	26.7	22.8	19.8	15.3	10.4	6.96	
25	2461	2327	2069	1571	1043	416	83.6	52.6	45.7	39.9	34.4	29.4	24.9	21.4	18.4	14.2	9.67	6.45	
30	2095	1930	1582	850	255	66.7	53.6	47.5	41.8	36.6	31.6	27.0	23.1	19.9	17.0	13.1	8.91	5.94	
35	1094	1000	820	451	152	55.7	47.3	42.2	37.4	32.7	28.4	24.5	21.0	18.2	15.3	11.8	7.90	5.28	
40	92.8	69.6	57.6	52.5	48.4	44.7	40.9	37.0	33.0	28.8	25.1	21.9	19.0	16.5	13.7	10.5	6.88	4.62	
45	66.9	54.9	48.3	44.9	41.9	38.9	35.6	32.1	28.7	25.3	22.3	19.6	17.2	14.8	12.0	9.22	5.92	3.97	
50	41.0	40.2	38.9	37.3	35.3	33.0	30.3	27.3	24.3	21.7	19.5	17.4	15.4	13.0	10.3	7.93	4.95	3.31	
55	34.1	33.5	32.5	31.2	30.0	28.1	25.5	23.2	21.0	19.0	17.2	15.3	13.4	11.1	8.80	6.60	4.08	2.78	
60	27.2	26.8	26.1	25.2	24.7	23.3	20.6	19.1	17.7	16.2	14.8	13.2	11.4	9.17	7.30	5.26	3.22	2.25	
65	22.2	21.8	21.3	20.7	20.4	19.7	17.6	16.3	15.0	13.8	12.4	10.9	9.27	7.51	5.88	4.22	2.67	1.91	
70	17.1	16.8	16.5	16.2	16.0	16.2	14.5	13.4	12.4	11.4	10.0	8.53	7.16	5.85	4.46	3.17	2.12	1.56	
75	13.0	12.9	12.7	12.6	12.6	12.8	11.5	10.4	9.38	8.48	7.41	6.33	5.32	4.39	3.40	2.47	1.80	1.39	
80	8.88	8.89	8.87	8.94	9.21	9.32	8.52	7.44	6.34	5.55	4.81	4.12	3.49	2.94	2.34	1.77	1.48	1.22	
85	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2017-11-09

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:7.290m [K=1.0000]
Remarks: